

## SEN300-TH

Temperature & Humidity Sensor



SEN300-TH is a compact environment monitoring sensor for measurement of temperature and humidity and transmitting data using LoRaWAN® technology. With this low power consumption technology, SEN300-TH can work up to 5 years with 4000 mAh battery. Combining with IQnexus LoRaWAN® gateway and IQnexus IoT Cloud solution, users can manage all sensor data remotely and visually.

SEN300-TH is widely used for both indoor and outdoor applications such as offices, hospitals, factories, greenhouses, etc.

### ◆ Features

- Embedded with Sensirion high-precision sensor chip
- Ultra-wide-distance transmission up to line of sight of 10km
- IP67 UV-resistant and waterproof enclosure for harsh environment applications
- Built-in 4000 mAh replaceable battery (space for second battery) 5-10 years without replacement
- Equipped with NFC for easily configuration
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with IQnexus IoT Cloud solution

## ◆ Specifications

Wireless Transmission	
Technology	LoRaWAN®
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)
Sensitivity	-147dBm @300bps
Mode	OTAA/ABP Class A
Measurement	
Temperature	
Range	-30°C to + 70°C
Accuracy	0°C to + 70°C (+/- 0.3°C), -30°C to 0°C (+/- 0.6°C)
Resolution	0.1°C
Humidity	
Range	0% to 100% RH
Accuracy	10% to 90% RH (+/- 3%), below 10% and above 90% RH (+/- 5%)
Resolution	0.5% RH
Operation	
Power On & Off	NFC, power button (Internal)
Configuration	Mobile APP(via NFC) or PC software(via USB Type-C)
Physical Characteristics	
Power Supply	1 × 4000 mAh ER18505 Li-SOCL <sub>2</sub> battery (extendable to 2 batteries)
Battery Life*	> 5 years (10 min interval, SF10), 10 years with 2 batteries
Operating Temperature	-30°C to +70°C
Relative Humidity	0% to 100% (non-condensing)
Ingress Protection	IP67
Dimension	88.5 × 85.3 × 27 mm (3.48 × 3.36 × 1.06 in)
Installation	Wall Mounting

\* Tested under laboratory conditions and for guideline purposes only. Also depends on the transmission cycle.